Yachting Solutions 229 Commercial Street Rockport, ME, US Phone: (207) 236-8100

AB Inflatables Profile A14-S

Boat Type: Inflatable



OVERVIEW

AB Inflatables introduces the all new swift water shallow V "AS-Series". AB is constantly looking at the needs in the Rescue and Commercial industries. This new versatile use series will get into shallow flood waters without fear of what is below as well as handling the swift waters of rivers or flooded streams. Combining the best of all worlds with marine grade aluminum and 1670 D-tex CSM fabric making them the most durable boat on the market. With their open design and a variety of seats and consoles they can be customized for any use.

Overall Length: 14' / 4,27m
Overall Beam: 6'5" / 1,96m
Inside Length: 10'10" / 3,3m
Inside Beam: 3'3" / 0,99m
Tube Diameter: 19" / 0,48m

• Person Capacity: 8

Weight: 317 lbs / 144 kg **

• Recommended HP: 40hp / 29.8kw

• Maximum HP: 50hp / 37.3kw

Shaft Length: 20" / 50,8cmRDC Design Category: C

(**) Weight spec applies for models without bow locker. Add 7 kg / 15 lbs for models 12-16.

SPECIFICATIONS

Basic Information

Manufacturer: AB Inflatables Boat Type: Inflatable

Model: Profile A14-S Hull Material: Aluminum

Year: 2017 Hull Type: Deep Vee

Category: Power

Dimensions & Weight

Length: 14.00 ft Draft - max:

LOA: 14 ft - 4.27 meter Bridge Clearance: -

Beam: 6 ft 5 in - 1.96 meter Dry Weight: 317 ft

Deadrise Aft: -

Tank Capacities

Fuel Tank: - Holding Tank: -

Fresh Water Tank: -

Accommodations

Total Cabins: - Crew Cabins: -

Total Berths: - Crew Berths: -

Total Sleeps: - Crew Sleeps: -

Total Heads: - Crew Heads: -

Captains Cabin: No

FEATURES

Standard Equipment

Marine Grade Aluminum Shallow "V" Hull

3 Heavy Duty Transom Knees

Welded Aluminum Stringer System

Non-Skid Rubber Floor Panels

Plastic External Transom Plate

Aluminum Internal Transom Plate

Aluminum Bow Eye

3-4 Aluminum Davit Lifting Points

Reinforced Aluminum Transom Tie Down & Towing Rings

Aluminum Bow Tie Down & Towing Rings

Deck Drain with Plug

Orca (CSM) 1670 Five Layer Coated Professional Use Fabric

Raised Double Solid Rub Rail

Push Plastic Non-Corrosive 2 Stage Inflation Valves

Pressure Relief Valves

1 Front & 4 Side Orca (CSM) Heavy Duty Fabric Handles on Tubes

Paddles with Aluminum Shaft

Paddle Holders

Hand Pump

Maintenance Kit

Owner's Manual

4 Layers Reinforced Seams

Rubber Protector on Full Length of Keel

3 Inch Drain Scuppers

Non-Skid (CSM) Coated Fabric On Tube Surface

Lifeline Around Tube

Optional Equipment

Bow Locker/Seat

Boat Cover

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

Fiberglass Console

Fiberglass Console with Forward Seat

Bench Seat with Storage

One Person Jockey Console

Two Person Jockey Console

Aluminum Console

Customized Aluminum Consoles, Jockey Consoles & Seats

Mechanical or Hydraulic Steering System

Stainless Steel Steering Wheel

Attachment

- Accessories and Parts
- CAD Drawing
- Chock & Davit Information

GALLERY











Yachting Solutions 229 Commercial Street Rockport, ME, US Phone: (207) 236-8100