Yachting Solutions
229 Commercial Street
Rockport, ME, US
Phone: (207) 236-8100

AB Inflatables Ventus 9 VL

Boat Type: Inflatable



OVERVIEW

Ventus – Latin for “air”– is our line of lightweight tenders. With their low weight to length ratio and balanced design, Ventus boats require very little horsepower to achieve astonishing performance and speeds. They sport a full V-shape hull that runs the entire length of the boat, providing exceptional tracking and stability. Ventus models are the only lightweight boats on the market with an additional air chamber built into the hull. This air chamber makes the Ventus line extremely safe and reliable, while providing a level non-skid floor to keep your cargo and passengers dry. Ventus boats make ideal tenders with plenty of room for carrying crew and provisions.

- Overall Length: 9' 6" / 2,90m
- Overall Beam: 5' 7 " / 1,72m
- Inside Length: 6' 9" / 2,06m
- Inside Beam: 2' 8" / 0,81m
- Tube Diameter: 17" / 0,43m
- Number of Chambers: 3+1
- Person Capacity: 4
- Weight: 106lbs / 48kg

- Recommended HP: 9,9hp / 7,4kw
- Maximum HP: 15hp / 11,2kw
- Shaft Length: 15" / 38,1cm
- RDC Design Category: C

SPECIFICATIONS

Basic Information

Manufacturer:	AB Inflatables	Boat Type:	Inflatable
Model:	Ventus 9 VL	Hull Material:	Fiberglass
Year:	2018	Hull Type:	Deep Vee
Category:	Power		

Dimensions & Weight

Length:	9.00 ft	Draft - max:	-
LOA:	9 ft 6 in - 2.9 meter	Bridge Clearance:	-
Beam:	5 ft 7 in - 1.7 meter	Dry Weight:	106 ft
Deadrise Aft:	-		

Tank Capacities

Fuel Tank:	-	Holding Tank:	-
Fresh Water Tank:	-		

Accommodations

Total Cabins:	-	Crew Cabins:	-
Total Berths:	-	Crew Berths:	-
Total Sleeps:	-	Crew Sleeps:	-
Total Heads:	-	Crew Heads:	-
Captains Cabin:	No		

FEATURES

Standard Equipment

Hand Laid Fiberglass Deep “V” Hull
Stringer System Laminated into Hull
Non-Skid Rubber Floor Panels
Plastic External Transom Plate
Aluminum Internal Transom Plate with Security Lip
Stainless Steel Bow Eye
3 Stainless Steel Davit Lifting Points
Inner Hull Drain with Plug
Deck Condensation Plug

Orca (CSM) Five Layer Coated Fabric
Raised Single Rub Rail
Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
Removable Rowing Seat
Oarlock Base
Telescopic Oars with Aluminum Shaft
Paddle Holders
Hand Pump
Maintenance Kit
Owner's Manual
Additional Air Retaining Chamber Under the Floor
3 Layers Reinforced Seams

Optional Equipment

Tube Chaps
Boat Cover
Chock Set
Bow Step with Fold Down Stainless Steel Cleat
Lateral Fold Down Stainless Steel Cleat
Removable Stern Seat

GALLERY







Yachting Solutions
229 Commercial Street
Rockport, ME, US
Phone: (207) 236-8100