



Yachting Solutions
229 Commercial Street
Rockport, ME, US
Phone: (207) 236-8100

AB Inflatables Ventus 10 VL

Boat Type: Inflatable



OVERVIEW

Ventus – Latin for “air”– is our line of lightweight tenders. With their low weight to length ratio and balanced design, Ventus boats require very little horsepower to achieve astonishing performance and speeds. They sport a full V-shape hull that runs the entire length of the boat, providing exceptional tracking and stability. Ventus models are the only lightweight boats on the market with an additional air chamber built into the hull. This air chamber makes the Ventus line extremely safe and reliable, while providing a level non-skid floor to keep your cargo and passengers dry. Ventus boats make ideal tenders with plenty of room for carrying crew and provisions.

- Overall Length: 10' 6" / 3,19m
- Overall Beam: 5' 7" / 1,72m
- Inside Length: 7' 7" / 2,31m
- Inside Beam: 2' 8" / 0,81m
- Tube Diameter: 17" / 0,43m
- Number of Chambers: 3+1
- Person Capacity: 5
- Weight: 123lbs / 56kg

- Recommended HP: 15hp / 11,2kw
- Maximum HP: 25hp / 18,7kw
- Shaft Length: 15" / 38,1cm
- RDC Design Category: C

SPECIFICATIONS

Basic Information

Manufacturer:	AB Inflatables	Boat Type:	Inflatable
Model:	Ventus 10 VL	Hull Material:	Fiberglass
Year:	2018	Hull Type:	Deep Vee
Category:	Power		

Dimensions & Weight

Length:	10.00 ft	Draft - max:	-
LOA:	10 ft 6 in - 3.2 meter	Bridge Clearance:	-
Beam:	5 ft 7 in - 1.7 meter	Dry Weight:	123 ft
Deadrise Aft:	-		

Tank Capacities

Fuel Tank:	-	Holding Tank:	-
Fresh Water Tank:	-		

Accommodations

Total Cabins:	-	Crew Cabins:	-
Total Berths:	-	Crew Berths:	-
Total Sleeps:	-	Crew Sleeps:	-
Total Heads:	-	Crew Heads:	-
Captains Cabin:	No		

FEATURES

Standard Equipment

Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Non-Skid Rubber Floor Panels
 Plastic External Transom Plate
 Aluminum Internal Transom Plate with Security Lip
 Stainless Steel Bow Eye
 3 Stainless Steel Davit Lifting Points
 Inner Hull Drain with Plug
 Deck Condensation Plug

Orca (CSM) Five Layer Coated Fabric
Raised Single Rub Rail
Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
2 Inside Stern Set of 2 Orca (CSM) Fabric Handles on Tubes
Removable Rowing Seat
Oarlock Base
Telescopic Oars with Aluminum Shaft
Paddle Holders
Hand Pump
Maintenance Kit
Owner's Manual
Additional Air Retaining Chamber Under the Floor
3 Layers Reinforced Seams

Optional Equipment

Tube Chaps
Boat Cover
Chock Set
Bow Step with Fold Down Stainless Steel Cleat
Lateral Fold Down Stainless Steel Cleat
Removable Stern Seat

GALLERY



Yachting Solutions
229 Commercial Street
Rockport, ME, US
Phone: (207) 236-8100