



McMichael Yacht Brokers
447 East Boston Post Road
Mamaroneck, NY 10543
Phone: 877.606.0401

AB Inflatables Profile A13-S

Boat Type: Inflatable



OVERVIEW

AB Inflatables introduces the all new swift water shallow V "AS-Series". AB is constantly looking at the needs in the Rescue and Commercial industries. This new versatile use series will get into shallow flood waters without fear of what is below as well as handling the swift waters of rivers or flooded streams. Combining the best of all worlds with marine grade aluminum and 1670 D-tex CSM fabric making them the most durable boat on the market. With their open design and a variety of seats and consoles they can be customized for any use.

- Overall Length: 13' / 3,96m
- Overall Beam: 6'5" / 1,96m
- Inside Length: 9'10" / 3m
- Inside Beam: 3'3" / 0,99m
- Tube Diameter: 18" / 0,46m
- Person Capacity: 7
- Weight: 282 lbs / 128 kg **
- Recommended HP: 30hp / 22.4kw

- Maximum HP: 40hp / 29.8kw
- Shaft Length: 20" / 50,8cm
- RDC Design Category: C

(**) Weight spec applies for models without bow locker. Add 7 kg / 15 lbs for models 12-16.

SPECIFICATIONS

Basic Information

Manufacturer:	AB Inflatables	Boat Type:	Inflatable
Model:	Profile A13-S	Hull Material:	Aluminum
Year:	2018	Hull Type:	Deep Vee
Category:	Power		

Dimensions & Weight

Length:	13.00 ft	Draft - max:	-
LOA:	13 ft - 3.96 meter	Bridge Clearance:	-
Beam:	6 ft 5 in - 1.96 meter	Dry Weight:	282 ft
Deadrise Aft:	-		

Tank Capacities

Fuel Tank:	-	Holding Tank:	-
Fresh Water Tank:	-		

Accommodations

Total Cabins:	-	Crew Cabins:	-
Total Berths:	-	Crew Berths:	-
Total Sleeps:	-	Crew Sleeps:	-
Total Heads:	-	Crew Heads:	-
Captains Cabin:	No		

FEATURES

Standard Equipment

Marine Grade Aluminum Shallow "V" Hull
 3 Heavy Duty Transom Knees
 Welded Aluminum Stringer System
 Non-Skid Rubber Floor Panels
 Plastic External Transom Plate
 Aluminum Internal Transom Plate
 Aluminum Bow Eye
 3-4 Aluminum Davit Lifting Points
 Reinforced Aluminum Transom Tie Down & Towing Rings

Aluminum Bow Tie Down & Towing Rings
Deck Drain with Plug
Orca (CSM) 1670 Five Layer Coated Professional Use Fabric
Raised Double Solid Rub Rail
Push Plastic Non-Corrosive 2 Stage Inflation Valves
Pressure Relief Valves
1 Front & 4 Side Orca (CSM) Heavy Duty Fabric Handles on Tubes
Paddles with Aluminum Shaft
Paddle Holders
Hand Pump
Maintenance Kit
Owner's Manual
4 Layers Reinforced Seams
Rubber Protector on Full Length of Keel
3 Inch Drain Scuppers
Non-Skid (CSM) Coated Fabric On Tube Surface
Lifeline Around Tube

Optional Equipment

Bow Locker/Seat
Boat Cover
Bow Step with Fold Down Stainless Steel Cleat
Lateral Fold Down Stainless Steel Cleat
Fiberglass Console
Fiberglass Console with Forward Seat
Bench Seat with Storage
One Person Jockey Console
Two Person Jockey Console
Aluminum Console
Customized Aluminum Consoles, Jockey Consoles & Seats
Mechanical or Hydraulic Steering System
Stainless Steel Steering Wheel

GALLERY



McMichael Yacht Brokers
447 East Boston Post Road
Mamaroneck, NY 10543
Phone: 877.606.0401