

# SABRE 38 Salon Express

## 2014 MODEL YEAR

Length (without anchor pulpit or swim platform)	38' 3"	11.7m
OAL (including swim platform and bow roller)	41' 9"	12.73m
Beam(overall)	13' 4"	4.06m
Draft	3' 4"	1.01m
Deadrise (at transom)	17 degrees	
Displacement (approx )	22,400 lbs.	10,181kg
Fuel capacity	300 gal.	1125L
Water capacity	100 gal.	380L
Holding tank capacity	40 gal.	150L
Headroom (maximum)	6'-6"	1.98m
Sleeping accommodations	4@6'-6"	4@1.98m
Optional berth in the main salon sleeps two.		
Height over waterline w/mast 13' 3"		4.04m
Built to CE Category B, NMMA, ABYC and USCG standards		

### STANDARD ENGINE/GEN SET SYSTEM

Twin Volvo Penta D4 300HP engines linked to VP IPS drives  
 3.7l (4) cylinder fresh water-cooled Includes Volvo electronic controls  
 Volvo Active Corrosion Protection system, GPS receiver and NMEA backbone  
 12V alternators each engine.  
 Volvo raw water intake strainers  
 Engine room blower.  
 Engine room vent ducts.  
 White gelcoated engine room  
 Mylar Foil face foam noise barrier.  
 6kW Koehler Generator

### FUEL SYSTEM

Twin 150 USG rotomolded diesel fuel tanks.  
 Racor fuel filters.  
 2" "Diesel" deck fill plate

### STEERING AND TRIM SYSTEMS

Volvo Penta IPS helm  
 Lenco Auto Glide trim tab system.

### HELM STATION

Single N Series Stidd helm chair  
 Volvo IPS electronic controls.  
 Engine Start/Stop control panel.  
 Volvo Penta color display (1) with:  
     Tachometer w/hour meter  
     Engine temperature  
     Engine oil pressure  
     Transmission oil pressure  
     Voltmeter  
     Water in fuel warning  
     Fuel remaining function  
     Fuel consumption function  
     Hi water temp and low oil pressure alarm  
 Triple windshield wipers with washers.  
 Compass  
 Switch controls for horn, running lights, anchor light, engine room blower and optional equipment.  
 Stazo wood trimmed 16" steering wheel

### 120VAC ELECTRICAL SYSTEM

Two 30 A. AC shore power inlets and two 50 ft. cords  
 Galvanic Failsafe isolator  
 Illuminated main circuit breaker distribution panel  
 120V outlets in each cabin and one in engine room.  
 All galley and head receptacles are GFI protected.  
 Additional outlets positioned in locations as appropriate Xantrex  
 60amp, 3-bank battery charger  
 Reverse cycle heat/ air conditioning in (2) zones.

### 12VDC ELECTRICAL DISTRIBUTION SYSTEM

Two dedicated engine starting batteries.  
 Two 4D 210 Amp hour deep cycle ship's service batteries.  
 Battery Management panel including  
     Emergency crossover switch.  
     Remote Control Ships Power switch  
     Remote Control Starting Battery switch  
 Illuminated main circuit breaker distribution panel w/battery voltage gauge  
 Lighting:  
     LED reading lights  
     LED lights in the overhead  
     LED strip lighting in appropriate locations  
     LED Engine room lighting  
     Cockpit courtesy lights w/remote switch at transom  
 UL Listed Tinned wire throughout.

### HULL COMPOSITE

"Vee" hull design with 24 degree deadrise amidships and 17 degrees at transom.  
 VIP Resin Infused laminate with ISO NPG white gelcoat and blended vinylester back-up resin.  
 Knitted Biaxial Structural E-Glass Reinforcements  
 SAN Corecell foam core in hull bottom and topsides.  
 Foam/plywood cored fiberglass stringer system.  
 Swim platform with under mounted telescoping ladder.  
 Hull side rubbing strakes.  
 PVC rub rail with stainless steel cap.  
 Painted (Urethane) Double Boot Stripe  
 Gold Cove Stripe

### DECK AND HARDTOP COMPOSITE

VIP resin infused, knitted Biaxial Structural E-Glass Reinforcements with balsa coring.  
 Molded in anti-skid deck surfaces.  
 Windows recessed into hard top  
 Port and starboard transom gates  
 Aft seating slides to expand cockpit dimension  
 Stainless steel anchor bowsprit roller system  
 Anchor lockers (2) with slam latches  
 (1) Large Aft hinged lazarette locker hatch with gas struts and (2) 3" dia compression latches for engine room access  
 Electronics pod at the helm station

### DECK HARDWARE

1 1/4" Diameter type 316 stainless steel perimeter rail system  
 (6) 12" Stainless Steel Cleats (2 fwd, 4 mid ship spring  
 (1) 10" Stainless Steel Cleat to starboard of windlass as anchor rode tie off.  
 Windlass with combination rope/chain gypsy  
 Single anchor roller sized for 35# CQR or Delta  
 Flagpole holder and flag staff.  
 Burgee staff on pulpit  
 Low Profile polished hatches w/screens (2) #44 on foredeck, (2) #10 port and starboard.  
 Custom stainless steel opening ports.  
 Teak cabin side eye-brow  
 Custom cast stainless steel "SABRE" medallion  
 Horn cleats in aft transom corners  
 Teak cap rails are optional

### HELM DECK

Stidd helm N Series helm seat  
 Wood in helm area is cherry  
 Two overhead pilot hatches with shades/screens  
 Bi-fold stainless steel companionway door with drop down window

### MASTER / FORWARD STATEROOM

Spacious Island Berth layout with 5" mattress. 3/4" laminated trim on berth top.  
 Cherry hull ceilings.  
 Drawers under bed. A/C return grills under drawers  
 Drawers in bureau w/locker w/shelf above and single louvered door.

Upper enclosed shelves with storage behind. Locker face with 2 doors. Each door to access partitioned space with shelves in the aft two compartments.  
Large Hanging Locker to starboard, cedar lined with shelf and hangar pole. Open shelf above louvered door.  
Teak and holly sole with 2 coats of sealer.  
Soft headliner panels.  
Passageway door between galley and forward cabin.  
Divider between galley and stateroom with surface mounted 26" LED Television on manual lift.

*Specifications subject to change without notice.*

July 2013

### **HEAD**

Vessel sink with faucet.  
Tempered Glass Shower stall with seat.  
Hot and cold pressure water.  
Electric shower sump pump.  
Storage locker.  
Solid Surface Material countertop with bull nose  
Towel bars.  
Wood trimmed mirror over sink  
Ventilation blower.

### **SALON**

Elevated "U" settee to port with Hi-gloss table with storage under.  
Mates L-shaped settee forward, open to galley with stainless steel hand rail.  
Cabinet to starboard with storage and LED TV on manual lift.  
Teak and holly sole w/ sealer.  
Sound deadening headliner panels.  
Optional settee and table that converts to berth.

### **GALLEY**

Solid Surface galley counter.  
Stainless steel sink with faucet.  
Drawers and storage lockers below counter.  
Storage cabinets outboard and above aft counter  
Lockers above stove.  
Two burner electric cook top  
Compact stainless steel microwave oven.  
Stainless steel drawer style refrigerator/freezer 12DC/120VAC

### **LOWER LOUNGE**

L-shaped settee with pull out converts to double berth.  
Bookshelf outboard of Settee.  
Extra large drawer handy to Galley for large items.  
Optional large 36" x 10" Hull Side fixed portlight.  
Optional Television/DVD combo for lower lounge.

### **FRESH WATER SYSTEM**

Water capacity 100 gals.  
11 gal. Stainless steel hot water heater 110V and engine heat exchanger  
Hot and cold water pressure system 12V.

### **DÉCOR**

Varnished cherry interior finish  
Screens on opening ports and hatches  
Optional fabric and drapery selections  
Laminated wood trims on counters and shelves  
Dovetailed maple drawer boxes

### **WASTE DISPOSAL**

Polyethylene holding tank with 40 gallon capacity  
Jabsco Quiet Flush fresh water MSD  
Diaphragm Waste pump on holding tank.

### **SAFETY**

Fire extinguishers, (4) at 2 1/2 lbs.  
Carbon Monoxide Detectors.  
Marelon sea valves on all below waterline fittings.  
Bonding system to safeguard against galvanic corrosion.  
Automatic fire extinguishing discharge system with override.  
Automatic 12V electric bilge pumps (3).  
High Water Alarms (3) for bilge.